

OptiView™ Integrated Network Analyzer: Specifications

Specs	
Weight Without External Battery	2.1 kilograms (4.6 lbs)
Weight With External Battery	2.8 kilograms (6.2 lbs)
Dimensions	26.0 x 23.4 x 6.4 centimeters (10.3 x 9.2 x 2.5 inches)
LCD Touch Screen Display	640 x 480 pixels, passive color panel, active area 157.42 mm x 118.06 mm, CCFT back-light and bezel, touch pad
LED Indicators	16 (21 with external battery)
Internal Battery	Lithium Ion 10.8V DC (nominal), 2.2Ah
External Battery	Lithium Ion 10.8V DC (nominal), 4.7Ah
External AC Adapter/Battery Charger	AC input: 120V - 240V, 50/60Hz, 1.5A DC output: 15V, 3.3A
Communication and Accessory Ports	2 USB, 1 multibus PCMCIA (PC Card type II), 1 DB-9 serial, 1 PS2 compatible keyboard, 1 PS2 compatible mouse
Network Analysis Ports	RJ-45 10/100BASE-T Ethernet Fiber 100 BASE-FX (OptiView Pro) Fiber 1000 BASE-X GBIC (OptiView Pro Gigabit)
Shock and Vibration	Meets requirements of MIL-PRF-28800F for Class 3 equipment
Laser	Class 1 Laser Product, complies with 21 CFR 1040.10 & 1040.11, CFR(J)